## CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION OFFICE OF THE STATE FIRE MARSHAL FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM

## FIRE ENGINEERING - BUILDING WATERIALS LISTING PRO

## LISTING SERVICE

**LISTING No:** 4175-0291:001 Page 1 of 1

**CATEGORY:** Roof Covering (Miscellaneous)

LISTEE: Crossfield, 3000 E. Harcourt St., Compton CA 90221

Contact: Ron Borum (310) 886-9100 Fax (310) 886-9119

DESIGN: Model Dex-O-Tex Weatherwear roof deck covering system: a built-up roof covering

consisting of a 15 lb. asphalt impregnated felt, stabilized synthetic rubber primer, Type 2 fiberglass mat, and acrylic masonry paint, with an thickness of 3/16" weighing approximately 2.0 lbs/ft². Refer to listee's data sheet for detailed product description and

operational considerations.

RATING: Class A

APPLICATION: Felt base (slip sheet) covered with a bond coat mixed 1 gal. of N-38 Latex to 18 lbs. of

hydraulic cement and extra fine aggregate, troweled to aggregate thickness allowed to drive for 1 hour. Bond coat covered with synthetic rubber at 12-25 lbs/ft² with Type 2 fiberglass mat pressed into primer and allowed to dry for 16 hours. Two coats of Noetex (1 gal. N-38 to 45 lbs. hydraulic cement and aggregate) troweled to approximately thickness of 3/32" and allowed to dry from 8-16 hours between coats. Two top coats (1 gal. of N-38 to 18 lbs. hydraulic cement and extra fine aggregate) applied over second coat of Neotex and allowed 1 hour drying time for first topping. Cover the entire assembly with one coat of Dex-O-Tex

color seal (red, green, gray, maroon, blue or tan).

**INSTALLATION**: In accordance with listee's printed installation instructions, applicable codes and ordinances

and in a manner acceptable to the authority having jurisdiction.

APPROVAL: Listed as a Class A roof covering system when constructed as described under

"Application".

Rev 03-27-96



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued: JUNE 13, 2003 Listing Expires June 30, 2004

Authorized By: **DIANE K. AREND**, Senior Deputy

Program Manager